

## **General Disclaimer**

### **One or more of the Following Statements may affect this Document**

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

NASA ~~CR~~ CR- 143829



ATS-6 MILLIMETER WAVELENGTH PROPAGATION EXPERIMENT

D. M. Theobald and D. B. Hodge

The Ohio State University

**ElectroScience Laboratory**

Department of Electrical Engineering  
Columbus, Ohio 43212

N75-29944

Unclas  
33001

G3/82

(NASA-CR-143829) ATS-6 MILLIMETER  
WAVELENGTH PROPAGATION EXPERIMENT Quarterly  
Report, 15 Oct. 1974 - 14 Jan. 1975 (Chio  
State Univ.) 16 p EC \$3.25 CSCI 20N

Report 3863- 4

April 1975

Quarterly Report for Period 15 October 1974-14 January 1975

Prepared for  
GODDARD SPACE FLIGHT CENTER  
Greenbelt, Maryland 20771



## NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

TECHNICAL REPORT STANDARD TITLE PAGE

1. Report No.	2. Government Accession No.	3. Recipient's Catalog No.
4. Title and Subtitle ATS-6 MILLIMETER WAVELENGTH PROPAGATION EXPERIMENT	5. Report Date April 1975	6. Performing Organization Code
7. Author(s) D. M. Theobald and D. B. Hodge	8. Performing Organization Report No. ESL 3863-4	10. Work Unit No.
9. Performing Organization Name and Address The Ohio State University ElectroScience Laboratory, Department of Electrical Engineering, Columbus, Ohio 43212	11. Contract or Grant No. NAS5-21983	13. Type of Report and Period Covered Quarterly Report 15 Oct. '74-14 Jan. '75
12. Sponsoring Agency Name and Address NASA Goddard Space Flight Center Greenbelt, Maryland 20771	14. Sponsoring Agency Code 60	
15. Supplementary Notes		
16. Abstract  The real time digital data acquisition system used to acquire ATS-6 propagation data at the OSU Fixed, Transportable, and Unmanned Terminals is described. This system performs all digital conversion, formatting, merging, and recording. All data from the remote sites are transferred to the Fixed Terminal for recording on a common digital tape.  The current status and summary of operations are also reviewed.		
17. Key Words (Selected by Author(s))  ATS-6 Millimeter Wave Propagation Diversity	18. Distribution Statement	
19. Security Classif. (of this report)  U	20. Security Classif. (of this page)  U	21. No. of Pages  13
		22. Price*

\*For sale by the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## CONTENTS

	Page
INTRODUCTION	1
DIGITAL DATA SYSTEM	1
DATA SYSTEM STRUCTURE	1
DATA RECORDING	4
OPERATIONS	5
CURRENT STATUS	6
REFERENCES	13

## INTRODUCTION

The primary objective of the ATS-6 Millimeter Wavelength Propagation experiment is the determination of reliability improvement resulting from the use of path diversity on millimeter wavelength earth-satellite communication links. This objective is being accomplished by measuring the path attenuation observed on 20 and 30 GHz ATS-6 downlinks at two spatially separated ground terminals.

Previous reports have described the complete experiment [1], the Transportable Terminal [2], and the Fixed Terminal [3] in detail. This report describes the digital data system which is used to digitize, format, merge, and record all data acquired. The current status of the experiment and summary of operations are also reviewed.

## DIGITAL DATA SYSTEM

All data acquired in this experiment are digitized and recorded on a common digital tape in real time. The data acquired at the remote terminals are digitized at the point of acquisition and transmitted to the Fixed Terminal via telephone lines. These data together with data from the High Resolution Radar/Radiometer System are merged and recorded on a single digital magnetic tape. In addition to these data, various status switches indicating operating modes and conditions are also monitored and recorded. The operator at the Fixed Terminal maintains control of the entire data system at all times.

## DATA SYSTEM STRUCTURE

The data acquisition system consists of an HP-2115-A minicomputer and control hardware, a digital magnetic tape deck, and two remote process controllers which are directed by the HP-2115-A via commercial telephone lines (Fig. 1). One remote controller located at the Transportable Terminal (Fig. 2a), acquires, buffers, and transfers data blocks at the request of the central computer. The data, sampled once a second, consist of status checks and the receiver and radiometer outputs from the Transportable Terminal. The remote controller, located at the Unmanned Terminal (Fig. 2b) samples one radiometer, interrogates a status register, samples test voltages, or performs a control function at the request of the central computer and returns the desired word of information once a second. The central computer must request each word of data or status separately and the remote controller returns the desired word after a 400 msec. delay. The central computer, in addition to controlling the remote processors, examines the status and samples the receivers and radiometers of the Fixed Terminal at rates of 10 or 200 samples per second, and records all data on magnetic tape.






Fig. 1. Fixed Terminal Data Acquisition System.




Fig. 2a. Transportable Terminal Data Acquisition System.




Fig. 2b. Unmanned Terminal Date Acquisition System.



The data acquisition system at each terminal consists of three types of control units, each tied to a computer or controller by a bus structure. The control units are addressed by and return data through the I/O and control bus. At the Transportable Terminal a Computer Automation Inc. LSI-II minicomputer serves as the controller; and at the Unmanned Terminal an inhouse designed and fabricated process controller serves this purpose. At the Fixed Terminal the control units are tied from a bus structure through a unit that emulates the LSI-II control and I/O functions to a duplex register in the HP-2115-A computer. This emulator allows the HP-2115-A to simulate an extended I/O instruction set, providing flexibility for adding or modifying units on the simulated bus and enabling control units of the same design to be used with either the LSI-II or HP-2115-A.

A/D conversion, status acquisition, and data transmission and reception are performed by the three control units. The analog signals are multiplexed and then converted. All A/D conversions provide seven significant bits plus sign. Provisions were made for sixteen sampled analog channels at the Fixed Terminal and eight at the Transportable Terminal. An A/D controller operates the A/D converter and multiplexer and provides an interrupt signal to the I/O bus.

Status levels are held in three sixteen-bit words (Table 2). The first status word for the Fixed and Transportable Terminals consists of the positions of a switch register upon which the operator indicates which units in the receiving system are functioning and are to be recorded and/or which function he wishes to perform with the operation program. Note that provision has been made to control the High Resolution Radar/Radiometer System at the Fixed Terminal through its digital control unit [4]. The program which controls this operation records the integrated video signal on a range bin-by-range bin basis from each radar every six-tenths of a second, depending upon the position of bits 6, 7, and 8. The second status word monitors conditions within the receivers and radiometers. The third status word at the Fixed Terminal accesses a modulo 1000 counter, which provides a time reference for the control program. The counter is synchronized to the seconds count of a DATATRON 3000 time code generator which is read through the radar control interface.

Data are transferred from the remote controllers to the Fixed Terminal data system via commercial voice-grade telephone lines. A pair of Vadic VA-1600 modems are used for data communication with the Transportable Terminal and two Bell System type 103 modems are used with the Unmanned Terminal. Modem controllers at each terminal provide the correct parallel-to-serial conversions, control, and interrupt logic.

#### DATA RECORDING

Several different record types are used to record the information from the various data sources. The record format (Table 1a) consists of a sixteen word header, followed by either sampled data or auxiliary data and then sampled data. Referring to Table 1b, the header contains the number of words in the record, the record type (Table 4)

<u>Record Type</u>	<u>Data Source</u>
3	K <sub>u</sub> -Band radar/radiometer
4	X-Band radar/radiometer
5	S-Band radar/radiometer
8	Transportable terminal
9	Fixed terminal-high rate
10	Fixed terminal-low rate
11	Unmanned radiometer

the three status words previously described, and the millisecond count of the record. Note that a change of status terminates a record independently of the number of data samples in the record. Hence, status information is maintained for the duration of a record and any change forces a new record to be written. The real-time-clock words, from the DATATRON 3000, are listed in Table 3. The fast queue interval (1/200 second) or slow queue interval (1/10 second) indicates the time between samples in the sampled data portion of the record, and word eleven indicates the number of samples in a record.

The data block following the header generally consists of sampled data from the 8-bit A/D converters whose outputs are Modified Two's Complements with  $\pm 5$  volt ranges. However, for radar records or Transportable Terminal records, auxiliary data, consisting of a fixed number of data or additional descriptive words, precedes the sampled data. The data block may have a variable length, with the number of words per record indicated in word 0 of the tape header. For sampled data, the sample time may be obtained from the header clock words and the queue interval. In addition, for the high rate data, a millisecond count preceding and following each sample is recorded with each A/D sample. These two times provide a measure of interval uncertainty for the sample if an interrupt from another device shifts the sample time. This information permits time skew to be determined during data reduction.

Data tapes at the Fixed Terminal are written according to the formats of Table 5. These tapes are subsequently transmitted to the Datacraft DC 6024 via a serial data link and are then recorded as fixed-length records. When read by a FORTRAN program, each DATACRAFT word (24 bits) contains an HP word (16 bits) right justified.

## OPERATIONS

Both the Fixed and Transportable Terminals remain operational. The total operating times of the four receivers at these two terminals as of February 15, 1975, were:

	<u>20 GHz</u>	<u>30 GHz</u>
Transportable Terminal	3,386 min.	4,364 min.
Fixed Terminal	2,187 min.	2,724 min.
Total Time:	12,661 min.	

#### CURRENT STATUS

The Transportable Terminal was moved to its remote site on March 13, 1975 and became operational at that location on March 15, 1975. This site is located 12.5 Km from the Fixed Terminal in approximately the northeast direction. The Unmanned Terminal was moved to its remote site on April 4, 1975 and became operational at that location on April 8, 1975. The Unmanned Terminal is located 13.4 Km from the Fixed Terminal in approximately the west direction. The separation distance between the Transportable and Unmanned Terminals is 13.4 Km. Data acquisition is continuing at these terminal locations.

Table 1a  
Tape Record Formats

Header
Sampled Data

A

Header
Auxilliary Data
Sampled Data

B

Table 1b  
Tape Record Header Format

Word  
Number

0	No. of words in record
1	Record type
2	Status word 1
3	Status word 2
4	Status word 3
5	Millisecond count
6	Clock word 1
7	Clock word 2
8	Clock word 3
9	Fast queue interval
10	Slow queue interval
11	No. of samples in record
12	Spare
13	Spare
14	Spare
15	Spare

Table 2  
Status Words

Bit No.	Word 1 Fixed Terminal	Word 2 Fixed & Transportable Terminal	Word 3 Fixed Terminal	Word 1 Transportable Terminal
0	20 GHz Receiver	0 dB	1	Unassigned
1	20 GHz Radiometer	10 dB	2	"
2	30 GHz Receiver	20 dB	4	"
3	30 GHz Radiometer	30 dB	8	"
4	20 GHz Receiver	Antenna	16	"
5	30 GHz Receiver	Hi Ref.	32	"
6	K <sub>u</sub> -band Radar/Radiometer	Lo Ref.	64	"
7	X-band Radar/Radiometer	Calibrate	.28	"
8	S-band Radar/Radiometer	0 dB	256	20 GHz Receiver
9	Record Transportable Terminal	10 dB	512	20 GHz Radiometer
10	Record & Calibrate unmanned radiometer	20 dB	Unassigned	30 GHz Receiver
11	Record unmanned radiometer	30 dB	"	30 GHz Radiometer
12	Unassigned	Antenna	"	Unassigned
13	Unassigned	30 GHz Radiometer	"	"
14	Idle	Lo Ref	20 GHz rcvr phase lock	20 GHz rec. phase lock
15	Stop	Calibrate	30 GHz rcvr phase lock	30 GHz rec. phase lock

Table 3  
Real-Time-Clock Words

Bit No.	Clock Word 1	Clock Word 2	Clock Word 3
0	1	1	1
1	2	2	2
2	4	4	4
3	8	8	8
4	1	1	1
5	2	2	2
6	4	4	4
7	8	8	8
8	1	1	1
9	2	2	2
10	4	4	4
11	8	8	8
12	Unassigned	Unassigned	Unassigned
13	"	"	"
14	"	"	"
15	"	"	"

Table 4  
Record Type Formats

- Types 3 ( $K_u$ -Radar), 4 (X-Radar), 5 (S-Radar)

Word No.

Record Contents

0																Auxiliary Data	
15	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1		0
16						Elevation angle											Auxiliary Data
17						S-band radiometer 8-bit bipolar 0-5 volts											
18						S-band power											
19						X-band radiometer											
20						X-band power											
21						K <sub>u</sub> -band radiometer											
22						K <sub>u</sub> -band power											
23						Clock word 1											
24						Clock word 2											
25						Clock word 3											
26						Azimuth word 1											
27						Azimuth word 2											
28	-Video Data Samples																Data
127	-32 integrations on an 8-bit, 10-5 volt A/D converter, each sample representing a 2 sec. range bin. Bit eleven indicates overflow																

- Type 8 (Transportable Terminal)

0																	Aux. Data
:																	
15	Header from Table 1																
16																	
17	Status word 1 from Table 2																Data
18	Status word 2 from Table 2																
19	Unassigned																
20	Transaction no., modulo 256																
21	Channel 0 (20 GHz receiver)								Channel 1 (20 GHz radiometer)								Data
22	Channel 2 (30 GHz receiver)								Channel 3 (30 GHz radiometer)								
23	Channel 4 (Wind speed)								Channel 5 (Wind direction)								
	Channel 6 (Rain gauge)								Channel 7								
.																	
.																	
.																	
.																	

\*Repeats a maximum of 20 times in one record; 8-bits bipolar 0-5 volts.



Table 4  
Continued

- Type 9 (Fixed terminal-high rate)

0																
.																
15	Header from Table 1															
** {	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
	msec count before the data								msec count after the sample							
	Channel 4 (20 GHz receiver)								Channel 5 (30 GHz receiver)							
	"															
18	"															
19																
.	.															
.	.															
.	.															

\*\*Repeats a maximum of 100 times in one record; 8 bits bipolar 0-5 volts

- Type 10 (Fixed Terminal-low rate)

0																
.																
15	Header from Table 1															
** {	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
	Channel 0 (20 GHz receiver)								Channel 1 (20 GHz radiometer)							
	Channel 2 (30 GHz receiver)								Channel 3 (30 GHz radiometer)							
	"															
18	"															
19																
.	.															
.	.															
.	.															

\*\*\*Repeats a maximum of 50 times in one record; 8 bits bipolar 0-5 volts.

- Type 11 (Unmanned radiometer)

0	Header from Table 1																	
.																		
.																		
15																	Aux Data	
16	Procedure type																	
17	Step no. of the procedure																	
18	Sample no. of the step																	
19	Unassigned																	
** {	20									Data (8-bits bipolar 0-5 volts)								Data
.										"								
.										"								
.										"								

Table 5  
Data Transmission Format

HP-2115-A Data Word

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
----	----	----	----	----	----	---	---	---	---	---	---	---	---	---	---

Data  
Program (PACI)

HP-2115-A  
Tape Word

	6	5	4	3	2	1	0
P	15	14	13	12	11	10	
P	9	8	7	6	5	4	
P	3	2	1	0	X	X	

Track No.

Character 1

Character 2 P-Parity

Character 3

Serial Link  
Programs (DUMS & DUMRT)

DC6024 Word

24															0									
X	X	X	X	X	X	X	X	X	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Fortran Tape Write

DC 6024  
Tape Word

	8	7	6	5	4	3	2	1	0
P	X	X	X	X	X	X	X	X	X
P	15	14	13	12	11	10	9	8	
P	7	6	5	4	3	2	1	0	

Track No.

Character 1

Character 2

Character 3

Note: All DC6024 records have a fixed length of 255 words.  
Files are preceded and terminated by a tape (file) mark.

## REFERENCES

- [1] D. B. Hodge, "ATS-F Millimeter Wavelength Propagation Experiment," Report 3863-1, July 1974, The Ohio State University ElectroScience Laboratory, Department of Electrical Engineering; prepared under Contract NAS5-21983 for National Aeronautics and Space Administration (NASA Goddard).
- [2] D. B. Hodge and R. C. Taylor, "ATS-G Millimeter Wavelength Propagation Experiment," Report 3863-2, September 1964, The Ohio State University ElectroScience Laboratory, Department of Electrical Engineering; prepared under Contract NAS5-21983 for National Aeronautics and Space Administration (NASA Goddard).
- [3] D. B. Hodge and R. C. Taylor, "ATS-6 Millimeter Wavelength Propagation Experiment," Report 3863-3, March 1975, The Ohio State University ElectroScience Laboratory, Department of Electrical Engineering; prepared under Contract NAS5-21983 for National Aeronautics and Space Administration (NASA Goddard).
- [4] D. B. Hodge and R. C. Taylor, "The Ohio State University ElectroScience Laboratory Radar/Radiometer Facilities for Precipitation Measurements," Report 2374-13, March 1973, The Ohio State University ElectroScience Laboratory, Department of Electrical Engineering; prepared under Contract NGR-008-080 for National Aeronautics and Space Administration (Office of Grants and Research Contracts).